



HCE HI

LAMBE SAFAR KA BHAROSEMAND SAATHI

> Lambi load body aur zyada power ke saath

> > BS6 P3))) Phase2

INCREASED PAYLOAD
OF 900 kg



LONGEST LOAD BODY OF 2 520 mm (8'2")



INCREASED POWER OF 26 kW



INCREASED PICKUP
OF 85 Nm



BIGGER 13" TYRES SIZE



TATA MOTORS



SPECIFICATIONS	
Engine Description:	TATA 800CC DICOR TCIC ENGINE, BS-VI, 4 stroke, Direct Injection, Common Rail, Turbocharged, Intercooled, Diesel engine
Engine Capacity	798 cc
Max Engine Output	26.0 kw @ 3 750 r/min
Max. Pickup	85 Nm @ 1 750-2 750 r/min
No. of Gears	S-Forward 1-Reverse
Clutch	Single plate dry friction diaphragm type
Steering	Mechanical, variable ratio
Front Suspension	Parabolic leaf spring
Rear Suspension	Semi - Elliptical leaf spring
Shock Absorber	Hydraulic double acting telescopic type
Tyres	155 R13 LT 8PR (Tubeless Tyres)
Max. Gradeability at rated GVW	36 %
Max. Speed	80 kmph
Gross Vehicle Weight	1 950 kg
Payload	900 kg
Fuel Tank Capacity	30 L
Urea Tank Capacity	10.5 L
Dimensions	
Length	4 075 mm
Width	1 500 mm
Height	1 858 mm
Wheelbase	2 250 mm
Min TCR	4 625 mm
Ground Clearance	160 mm
Cargo Box Dimensions	2 520 mm x 1 490 mm x 300 mm
Seating	D+1









EXTRA FEATURES FOR EXTRA COMFORT

















The illustrations and photographs may show accessories and items of optional equipment which are not part of the standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement. Terms & conditions apply.