

## **Technical Specifications**

Models	710 LPT CX DCR 100 B6M5 ST			
Engine	4SP BS6 Phase2 TCIC engine			
Engine Type	4 Cylinder in line water cooled direct Injection diesel engine with intercooler			
Engine Displacement	2 956 cc			
Power	74.5 kW (100 Ps) @ 2 800 r/min			
Torque	300 Nm @ 1000 - 2 200 r/min			
Clutch	Single plate dry friction type - 280 mm dia			
Gearbox	G400 (5F, 1R), Cable Shift Mechanism			
Gearbox Ratio	1st - 6.45, 2nd - 3.66 , 3rd- 2.29, 4th -1.49, 5th - 1.00, Rev- 6.26			
Suspension - Front Type	Parabolic Suspension with rubber bush and Hydraulic double acting telescopic shock absorbers			
Suspension - Rear Type	Semi-Elliptical Leaf Spring with Aux Springs			
Tyres	Radial 8.25 R 16 Low CRR Tyre (FR - 2, RR - 2, Spare - 1)			
Cabin Type	Fully Forward Cabin (LPT)			
Steering Type*	Power Steering (4 Spoke)			
Brakes Type	Dual Circuit Full Air S" Cam Brakes With Auto Slack Adjuster (Drum - Drum) - 325 mm			
Ground Clearance	220 mm			
Gradeability	25 %			
Rear Axle	Banjo Type - Single reduction Hypoid gears, fully floating axle shafts - RAR: 4.85			
Battery	12 V, 100 Ah capacity with 120 A Alternator			
Fuel Tank Capacity	90 l HD Polymer Fuel Tank with Fuel Mangement			
Load Body Variants	CAB & HSD			
GVW	7 490 kg			
FAW	3 640 kg			
RAW	3 850 kg			
Long member Size (LxBxH)	200 mm x 60 mm x 5 mm			
Wheelbase	3 550 mm		3 920 mm	
TCD		14 200 mm	17 000 mm	
Variants	CAB	HSD	CAB	HSD
Load Body Dimenssions (LxWxH)	-	4 347 mm x 2 117mm x 1 825 mm	-	5 218 mm x 2 117 mm x 1 820 mm
Warranty	3 years or 3 00 000 km			
Seating Capacity	D + 2			
DEF Tank Size	18 L			
FIP Model	Delphi CR System (1800 bar pressure)			

## **Key Features & Benefits**



LPT Wide Cabin





Fleetedge Telematics



Firmware Over The Air

## **Applications**











Cement, Building Parcel & Courier Construction

E Commerce

Pharma

Fruits & Vegetables

FMCG









& Reefers





## **TATA MOTORS**

To know more, visit your nearest Tata Motors dealership

www.light-trucks.tatamotors.com





