

for immediate use

PRODUCT NOTE

Tata Ultra Sleek T.6 - Dil Se Smart Truck!

Now Business Will Reach Every Corner

The Tata Ultra T.6 is the latest offering from Tata Motors in Light Commercial Vehicle (LCV) segment in 6-6.5 tonne GVW category. It features the world-class vehicle range of the Ultra Sleek cabin. It is India's first International-standard Sleek Cabin, measuring 1900mm in width and is designed and developed for Indian roads, redefining the transportation industry, with a perfect blend of latest technology and economies of operations. The sleek cabin helps in negotiating tight bends and congested, narrow roads, reducing the turnaround time, and thus allowing the transporter to reduce the turnaround time. It enables best-in-class driving comfort for the drivers. Its compactness also makes these trucks easier to drive, park, and consequently better suited for urban, semi-urban transportation. The cabin is designed thoughtfully with walk-through features, roomy interiors and 1+2 seating. It is developed to delight both, the fleet owners as well as the driving fraternity.

The Ultra Sleek T.Series is built around the 'Power of 6' philosophy of Tata Motors BS6 I&LCV range with focus on: Power of Business Profit, Power of Vehicle Performance, Power of Driving Comfort, Power of Convenience & Connectivity, Power of Value and Power of Safety and Security.

Feature Highlights:

- New Generation (NG) Sleek cabin with appealing, futuristic styling & Aerodynamic design Wider version has won the Prestigious CII's "Design Excellence Award"
- Modular design with walk through features, ergonomically designed with liberal storage space
- Enhanced safety features meeting European safety norms
- Provides complete panoramic view to driver to avoid blind spots
- · Dash mounted gear shift lever with cable shift mechanism
- Tilt & Telescopic Power steering
- Better EBHS, better NVH, superior heat and noise insulation
- Advanced H2LS braking for highest safety
- Parabolic leaf springs to negotiate any terrain
- Smaller wheelbase of 2900 mm to provide best-in-class TCD for convenient narrow lane applications
- Both 4-tyre and 6-tyre combinations offered in 10 feet load decks. Another variant of 14 feet with 4-tyre configuration is also being offered
- Clear-lens headlamps and LED tail-lamps to enhance the look
- Music system with Blaupunkt speakers, USB fast Charging
- Bucket type adjustable driver seat

USPs that impact the Total Cost of Ownership:

- The Ultra Sleek T.6 delivers faster turnaround time, higher payload capacity, easier manoeuvrability coupled with stylish and comfort rich cabin
- The proven 4-cylinder 4SPCR Engine delivers 100PS and 300Nm torque @ 1200-2200 rpm
- Higher maximum torque (300 Nm Torque @ 1200-2200 r/min) combined with high low end torque (290 Nm Torque
 @ 1200-2200 r/min) over a wide range of engine speeds deliver comfortable drivability. This facilitates requires lesser gearshifts for pleasant driving experience and high gradient climbing ability
- Equipped with New generation Gearbox GB400 apt for providing for higher payload and better durability, has been designed with a Higher Torque to Weight Ratio and an Integral clutch housing
- Strongest chassis in its class, with bolted design for increased modularity rolled from HSS 800 (high strength steel with high tensile strength) coupled with straight long member –multiple wheelbase options available

Applications Suitable for:

E-Commerce, Logistics Services, Couriers, Pharma, Reefers (fresh delivery of perishable goods), White goods, FMCG, LPG Cylinder carriers, Water Tanker, Poultry, Fruits, Vegetables and Municipal applications.





for immediate use

PRODUCT NOTE

Technical specifications:

Parameter		Tech Specification		
Cabin	Ultra Narrow Cab (D+2)	Ultra Narrow Cab (D+2) seating- Crash Tested 1.9 Mt. wide walkthrough all Steel Make cabin with Panoramic View		
Engine		4SPCR BS6		
Danier and Tarrie		100PS @2800 r/min		
Power and Torque		300 Nm @ 1200 -2200 r/min		
Transmission	G400, 5	G400, 5 Speed, Manual Synchromesh Gearbox (5F, 1R), PTOP		
Clutch		Single plate dry friction Type , 280mm dia		
Steering		Power Steering- Tilt and Telescopic		
Brakes		Hydraulic two leading slide shoe		
Suspension		Front – Parabolic springs		
		Rear – Semi-Elliptical Leaf Springs		
Battery		12V, 100 Ah capacity		
Tyres		Bias Tyre/ Radial Tube tyre		
Gradeability		35 %		
Load body		HDLB and CABIN CHASSIS		
		Variants		
Wheel Base	2950	3550	2950	
GVW	6450	6450	6450	
Tyre combinations	4 Tyre	4 Tyre	6 Tyre	
Tyre Size	8.25 X 16LT 16 , 14 PR /	8.25 X 16LT 16 , 14 PR	7.5 X 16LT 16 , 14 PR	
	8.25R16LT 16 , 14 PR	/8.25R16LT 16 , 14 PR	/7.5R16LT 16 , 14 PR	
Ground Clearance	220	220	196	
Load Body Size	10 Ft X 6.3 Ft	14 Ft X 6.3 Ft	10 Ft X 6.3 Ft	